

serie

L

# PELLE RÉTRO

BACKHOE • RETROEXCAVADORA



### L / DigDig

- STABILISATEURS RIGIDES (OBLIGATOIRE)
- LOCKING TENSIONER (MANDATORY)
- TENSORES ENTUMECIMIENTO OBLIGATORIOS



- TOURILLONS/DOUILLES CÉMENTÉS ET RECTIFIÉS
- HARDENED AND RECTIFIED PINS/BUSHINGS
- PERNOS Y BUJES CEMENTADOS Y RECTIFICADOS



- BLOCAGE HYDRAULIQUE
- HYDRAULIC LOCK-UP
- BLOQUEO HIDRAULICO

### MOD. TIX

- MULTIPOSITION DE TRAVAIL
- WORKING MULTIPositionING
- MULTIPOSICION DE TRABAJO

## CARACTÉRISTIQUES SPECIFICATIONS / DATOS TÉCNICOS

| MOUVEMENT DES BRAS<br>ARM MOTION / MOVIMIENTO BRAZOS |   | 18<br>TIX   | 19<br>TIX | 21<br>TIX | 22<br>TIX |
|--|---|-------------|-----------|-----------|-----------|
| A  | (mm.) A   | (mm.) 1800  | 1900      | 2200      | 2300      |
| B  | (mm.) B   | (mm.) 1800  | 1800      | 2200      | 2200      |
| C  | (mm.) C   | (mm.) 2600  | 2600      | 2900      | 2900      |
| D Rayon d'action                                     | (mm.) D Working radius<br>Rayo de acción                  | (mm.) 2700  | 2750      | 3000      | 3050      |
| Largeur du châssis avec translation                  | (mm.) Traveling frame width<br>Ancho bastidor trasladable | (mm.) 1200  | 1500      | 1200      | 1500      |
| Force d'arrachement                                  | (kg.) Bucket breakout force<br>Fuerza de tiro al diente   | (kg.) 2000  | 2000      | 2200      | 2200      |
| Angle de rotation                                    | Rotation angle<br>Angulo de rotación                      | 180°        |           |           |           |
| Débit max pompe                                      | (lt/min) Pump max delivery<br>Capacidad máx. de la bomba  | (lt/min) 15 | 15        | 20        | 20        |
| Pression de travail                                  | (Bar) Working pressure<br>Presión de taraje               | 180         |           |           |           |
| Capacité du réservoir                                | (lt.) Tank capacity<br>Capacidad depósito                 | 25          |           |           |           |
| Benne d'excavation                                   | (mm.) Digging bucket<br>Cuchara excavación                | 250+400     |           |           |           |
| Poids avec godet                                     | (Kg.) Weight with bucket<br>Peso con cuchara              | (Kg.) 380   | 400       | 430       | 450       |
| Poids min. tracteur                                  | (kg.) Min. tractor's weight<br>Masa mínima tractor        | (kg.) 1300  | 1400      | 1500      | 1600      |
| Puissance min. requise                               | (HP) Min. power requirements<br>Potencia mínima tractor   | (HP) 18     | 18        | 22        | 22        |

